

Latex exam gloves, offering robust personal protection and secure grip

- **Durable latex:** Soft, stretchable latex provides tough chemical splash protection and superior comfort
- **Secure grip:** These latex medical exam gloves have been developed with textured fingertips for a confident grip even when handling slippery, oily objects
- **Enhanced finger thickness:** 0.20 mm/7.9 mil finger thickness results in greater protection from snags, tears and rips when compared with standard latex alternatives
- **Elevated comfort:** An extra wash during manufacturing makes these gloves smooth, comfortable and are easy to don



CAUTION: This product contains natural rubber latex, which may cause allergic reactions

Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Machinery and Equipment
- Healthcare

Recommended For

- Inspection, selecting, checking parts
- General Purpose Auto Aftermarket
- Oil, fluids and filter change
- Engine transmission and repair
- Tire rotation & changes
- Maintaining lab furniture and equipment
- Sample taking and processing
- Raw material sample collection
- Inspection (picking, checking and marking)
- Standard, moderate risk examination procedures

TECHNICAL DATA SHEET

| Product Information | |
|------------------------|--|
| External Glove Surface | Textured Fingers |
| Audit Standards | EN ISO 13485:2012 |
| Packaging Overview | 100 gloves per dispenser 10 dispensers per case 1000 gloves per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Malaysia |
| Product Segmentation | Robust |
| Antistatic | Not Tested |
| Silicone Free | No |

PHYSICAL PROPERTIES

| | Typical Values | | Testing Method |
|---|---------------------|--------------------|---------------------|
| Length (mm/inches) | 245 / 9.6 | | ASTM D3767,EN 420 |
| Freedom from Holes (Inspection level I) | 1.5 AQL | | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils) | 0.16 / 6.3 | | ASTM D5151,EN 455-2 |
| Finger Thickness (mm/mils) | 0.20 / 7.9 | | ASTM D5151,EN 455-2 |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | ≥ 30 | ≥ 21 | ASTM D412 & D573 |
| Elongation at Break (%) | ≥ 750 | ≥ 600 | ASTM D412 |
| Force at break (N) | ≥ 16 | ≥ 6 | EN 455-2 |

ORDERING INFORMATION

| Size | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | MF-300-XS | MF-300-S | MF-300-M | MF-300-L | MF-300-XL |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

BR +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

