


Neoprene chemical-resistant gloves, protecting users against cytotoxic/chemotherapy drugs

- **Specialized protection:** MICROFLEX NeoPro® EC NEC-288 neoprene disposable gloves provide chemical splash protection in high-risk environments, and are specifically tested against cytotoxic/chemotherapy drugs*
- **Strong grip:** Their neoprene formulation and textured fingertips enhance grip performance in both wet and dry conditions
- **Easy donning:** Polymer-coated, MICROFLEX NeoPro® EC gloves are easy to don
- **Certified performance:** These gloves meet National Fire Protection Association 1999 Emergency Medical Glove Requirements, indicating they are approved for use by first responders in the US
- **Extended protection:** An extended cuff offers wearers additional forearm and wrist protection



*see product packaging for details

Industries

- Life Sciences
- Chemical
- Healthcare

Recommended For

- Animal care feeding and cleanup
- Maintaining lab furniture and equipment
- Spill or leakage cleanup
- Transferring liquids and solids
- Assembly of parts
- Sample taking and processing
- Administering drugs
- Raw material sample collection
- Testing
- Maintenance
- Tested for use with chemotherapy drugs
- Enhanced grip in wet environments
- Extra protection over the wrist and arm
- Damp donning
- Protection from Type I latex allergy in HCW's or patients
- Higher-risk clinical applications
- Protection from Type I latex allergy in HCW's or patients

TECHNICAL DATA SHEET

Product Information	
External Glove Surface	Textured Fingers
Audit Standards	EN ISO 13485:2012
Packaging Overview	50 gloves per dispenser 10 dispensers per case 500 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Indonesia
Product Segmentation	High Risk
Antistatic	Yes
Silicone Free	No

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	290 / 11.4		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.16 / 6.3		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.21 / 8.3		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	24	20	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 500	ASTM D412

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	NEC-288-S	NEC-288-M	NEC-288-L	NEC-288-XL	NEC-288-XXL

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

BR +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

